# PowerCat™ A33

## New Materials Creating New Performances

Quality Products.

Dependable Service.

### INTRODUCTION

PowerCat<sup>™</sup> A33 is an amine catalyst which consists 33% triethylene diamine dissolved in 67% dipropylene glycol, it can provide a high level of activity and good physical properties to flexible foam systems.

## **FEATURES**

- ☐ Strong efficiency gel amine catalyst
- ☐ Suitable for various flexible foam

#### PHYSICAL PROPERTIES

Appearance	Clear liquid	
Viscosity 25°C	100+/20 cSt	
Density <sub>25°C</sub>	1.03 g/cm <sup>3</sup>	
Flash Point	>88 °C	

## PACKING

PowerCat<sup>™</sup> A33 is supplied in 25Kg pail.

When stored at ambient temperature in the original unopened packing, PowerCat<sup>™</sup> A33 has a shelf life of 24 months from the date of production.

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing. We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

Copyright © TinToll Performance Materials Co., Ltd. www.TinToll.com.

