

SiSiB[®] SR1020

Methyl Hydrogen Silicone Resin

INTRODUCTION

SiSiB[®] SR1020 can be used for producing LED patch adhesive, electronic adhesive and liquid adhesive.

TYPICAL PHYSICAL PROPERTIES

Appearance	Colorless Clear Liquid
Viscosity (25°C, cP)	290-310
Hydrogen Content (%)	0.70-0.80
M/Q	0.8-1.0
Refractive Index (25°C)	1.4000-1.4200
Volatile (150°C, 3h, %)	Max.3.0

SPECIAL FEATURES AND BENEFITS

SiSiB[®] SR1020 is suitable for the preparation of optical silicone rubber.

SiSiB[®] SR1020 has excellent reinforcing effects.

Liquid adhesives prepared with SiSiB[®] SR1020 provide excellent mechanical properties and transparency.

Thermally conductive adhesives prepared with SiSiB[®] SR1020 have good reinforcing effects and low viscosity.

PACKING AND STORAGE

SiSiB[®] SR1020 is packed in 25Kg Pails.

In the original unopened packaging, SiSiB[®] SR1020 has a shelf life of 12 months in a dry and cool place.

NOTES

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further

SiSiB[®] SR1020

Methyl Hydrogen Silicone Resin

developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

July 2024 | [Technical Data Sheet](#) | [Edition SR](#)

Please send all technical questions concerning quality and product safety to:
support@SiSiB.com.