

ADDSiL™ 1390 Mar Resistance Additive

INTRODUCTION

ADDSiL™ 1390 is a high molecular weight silicone dispersion which provides excellent slip and release in water-borne systems.

ADDSiL™ 1390 can improve the mar resistance property of the coating film.

EFFECTS

Leveling:	★★★
Wetting:	★★★
Recoat Ability:	★★★★★
Compatibility:	★★★
Slip effect:	★★★★★
Low Foaming Stability:	★★★★
Anti-crater:	★★★
Anti-adhesive:	★★★★★

PHYSICAL PROPERTIES

Color and Appearance	Viscous ointment liquid
Ingredient	Dispersion of high molecular weight silicone
Content	80%
Solvent	Water

APPLICATIONS

Water-borne coatings.

RECOMMENDED DOSAGE

The recommended dosage is 0.1% ~ 1.0% during the production.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

PACKING

ADDSiL™ 1390 is supplied in 25Kg pail.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

ADDSiL™ 1390 Mar Resistance Additive

STORAGE

In the original unopened packaging, ADDSiL™ 1390 has a shelf life of 24 months.

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.