

ADDSiL™ 5106 ANTI-GRAFFITI & EASY-CLEAN

INTRODUCTION

Silicone modified acrylic dispersion

PHYSICAL PROPERTIES

Color and Appearance	Milky white liquid
Solvent	Water/ DPM/DPNB
Active Ingredient 120°C, 1h	38-44%
Density 25°C	1.03-1.07 g/cm ³
Viscosity 25°C	5-50s (TU-4 viscometer)
Hydroxyl value	135-145 mg KOH/g
pH	6.5-7.5

BENEFITS

- Low VOC.
- Increase slipping, hydrophobicity, oleophobicity.
- Excellent anti-fouling performance.
- Excellent ability of chemical and solvent resistance.
- Good weather resistance.
- Fast drying. Long activation period.

APPLICATIONS

Water-borne coating

Typical dry condition: 80°C, 1-2h

ADDSiL™ 5106 also has a good effect after self-drying, and the performance can be fully reflected after curing for more than one week.

PACKING

ADDSiL™ 5106 is supplied in net weight 180Kg drum.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

In the original unopened packaging, ADDSiL™ 5106 has a shelf life of 6 months in a dry and cool place.

ADDSiL™ 5106 ANTI-GRAFFITI & EASY-CLEAN

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.