

ADDSiL™ 5109 ANTI-GRAFFITI & EASY-CLEAN

INTRODUCTION

ADDSiL™ 5109 is silicone modified polyurethane acrylic resin.

PHYSICAL PROPERTIES

Color and Appearance	Transparent to yellowish liquid
Solvent	BAC
Active Ingredient _{120°C, 1h}	95%
Density _{25°C}	1.00-1.04 g/cm ³
Viscosity _{25°C}	200-1000 cP

BENEFITS

- Increase slipping, hydrophobicity and oleophobicity.
- Anti-marker wiping performance.
- High hardness and transparency.
- Excellent lotus leaf effect.
- Water contact angle >100°C.
- Excellent adhesion on the surface of PET/PVC.
- Improve the scratch resistance and abrasion resistance.
- Excellent solvent resistance.
- Low VOC.

APPLICATIONS

UV curing coating

PACKING

ADDSiL™ 5109 is supplied in net weight 180Kg drum.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

In the original unopened packing, ADDSiL™ 5109 has a shelf life of 24 months in a dry and cool place.

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

ADDSiL™ 5109 ANTI-GRAFFITI & EASY-CLEAN

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.