

ADDSiL[™] 6071 ANTI-GRAFFITI ADDITIVE

INTRODUCTION	ADDSiL [™] 6071 is a special modified silicone with acrylic group which is suitable for UV coating system. ADDSiL [™] 6071 can provide excellent anti-block and anti-graffiti effect.	
PHYSICAL PROPERTIES	Color and Appearance	Yellowish liquid
	Ingredient	Modified silicone
	Active Content	100%
BENEFITS	 Decrease the surface tension. Accelerate the wetting ability. Excellent anti-block effect. Excellent anti-graffiti effect. 	
APPLICATIONS	ADDSiL [™] 6071 is suitable for UV coating system. The recommended dosage is 0.1%-1.0% of the total formulations.	
PACKING	ADDSiL™ 6071 is supplied in net weight 25Kg Pail.	
HANDLING	This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.	
STORAGE	In the original unopened packing, ADDSiL™ 6071 has a shelf life of 12 months in a dry and cool place.	
NOTE	All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.	

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

SINOPCC GROUP

Product Data Sheet - Page 1/2 ADDSiL™ 6071 December 2024, Version 8.1, D-W Copyright © SiSiB SILICONES. Affiliate of SINOPCC GROUP. www.sinosil.com



ADDSiL[™] 6071 ANTI-GRAFFITI ADDITIVE

We disclaim liability for any incidental or consequential damages.

SINOPCC GROUP

Product Data Sheet - Page 2/2 ADDSiL[™] 6071 December 2024, Version 8.1, D-W Copyright © SiSiB SILICONES. Affiliate of SINOPCC GROUP. www.sinosil.com