

ADDSiL™ 5024 Silicone Defoamer

INTRODUCTION

ADDSiL™ 5024 is organic silicone defoamer for water-based systems. It has excellent defoaming ability with little addition, and it appears very well.

PHYSICAL PROPERTIES

Color and Appearance	Colorless, viscous liquid
Ingredient	Modified Polydimethylsiloxane
Content	100%

APPLICATIONS

Water based and middle/high polarity oil coating systems

RECOMMENDED DOSAGE

The recommended dosage is 0.05%-1.0% of the total formulations. The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

To achieve optimal defoaming, ADDSiL™ 5024 should be added in grinding stage.

PACKING

ADDSiL™ 5024 is supplied in 25Kg plastic pail or 180Kg steel drum.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, ADDSiL™ 5024 has a shelf life of 24 months from the date of production.

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

ADDSiL™ 5024 Silicone Defoamer

We disclaim liability for any incidental or consequential damages.