

ADDSiL™ 5025 Silicone Defoamer

INTRODUCTION

ADDSiL™ 5025 is an organic silicone defoamer. It provides excellent antifoam property in grinding process.

PHYSICAL PROPERTIES

Color and Appearance	Colorless viscous liquid
Ingredient	modified Polydimethylsiloxane
Solvent	DPM
Content	60%

BENEFITS

- Excellent defoaming ability at a low dosage.

APPLICATIONS

ADDSiL™ 5025 can be used in water based and middle/high polarity oil coating systems.

RECOMMENDED DOSAGE

ADDSiL™ 5025 should be charged at the lapping stage during the produce with 0.05%-1.00% dosage to gross under normal conditions.

PACKING

ADDSiL™ 5025 is supplied in 25Kg plastic pail or 180Kg steel drum.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, ADDSiL™ 5025 has a shelf life of 24 months from the date of production.

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

ADDSiL™ 5025 Silicone Defoamer

We disclaim liability for any incidental or consequential damages.