

ADDSiL™ 5065 Silicone Defoamer

INTRODUCTION

ADDSiL™ 5065 is an organic silicone antifoam emulsion used for water-based systems which disperses easily and has lower possibility to cause crater.

ADDSiL™ 5065 is suitable for coating and printing ink systems with high viscosity.

PHYSICAL PROPERTIES

Color and Appearance	White emulsion
Ingredient	Modified silicone
Solvent	Water
Content	50%

BENEFITS

- Suitable for water-based coating systems
- Fast defoaming and foam inhibition ability at a low dosage

APPLICATIONS

ADDSiL™ 5065 is recommended to use in the water-based coating systems.

RECOMMENDED DOSAGE

ADDSiL™ 5065 should be charged at the lapping stage during the produce with 0.05%-1.00% dosage to gross under normal conditions.

PACKING

ADDSiL™ 5065 is supplied in 25Kg plastic pail or 180Kg steel drum.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, ADDSiL™ 5065 has a shelf life of 24 months from the date of production.

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

ADDSiL™ 5065 Silicone Defoamer

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.