

# ADDSiL™ 5066 Silicone Defoamer

## INTRODUCTION

ADDSiL™ 5066 is a fluorine modified organic silicone antifoaming agent with excellent inhibition and defoaming ability. Therefore, it can decrease the amount of bubble greatly during the coating manufacture and in the application stage.

## PHYSICAL PROPERTIES

Color and Appearance	Colorless transparent liquid
Active Ingredient	Fluorine modified organic silicone compound
Component	1%
Solvent	Isooctyl acetate

## BENEFITS

- Excellent defoaming
- Superb compatibility
- No influence on the transparency of paint film
- Comprehensive applications

## APPLICATIONS

ADDSiL™ 5066 can be used in various common coating systems.

ADDSiL™ 5066 is suitable for all solvent systems.

## RECOMMENDED DOSAGE

The recommended dosage is 0.1-1.0% of the total formulations at random stage during the produce.

## PACKING

ADDSiL™ 5066 is supplied in 25Kg steel drum.

## HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

## STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, ADDSiL™ 5066 has a shelf life of 24 months from the date of production.

## ADDSiL™ 5066 Silicone Defoamer

### NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.