

# ADDSiL™ 5367 Silicone Defoamer

## INTRODUCTION

ADDSiL™ 5367 is fluorine modified organic silicone antifoaming agent which is suitable for solvent-borne systems.

ADDSiL™ 5367 provides excellent abilities to restrain and break the bubble. It can greatly reduce the amount of bubble during the coating production or the using stage.

## PHYSICAL PROPERTIES

Color and Appearance	Colorless transparent liquid
Ingredient	Fluorine modified organic silicone compound
Active content	1%
Solvent	Isoctyl acetate

## BENEFITS

- Excellent defoaming
- Superb compatibility
- No influence on the transparency of paint film
- Comprehensive applications

## APPLICATIONS

- Solvent- borne system

## RECOMMENDED DOSAGE

The recommended dosage is 0.1%-1.0% during the production. The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

## PACKING

ADDSiL™ 5367 is supplied in 25Kg Pail.

## HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

## STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, ADDSiL™ 5367 has a shelf life of 24 months from the date of production.

## ADDSiL™ 5367 Silicone Defoamer

### NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.