

ADDSiL™ 5371 Silicone Defoamer

INTRODUCTION

ADDSiL™ 5371 is a silicone defoamer for water-based coatings that offers excellent defoaming capabilities at low dosage levels.

PHYSICAL PROPERTIES

Color and Appearance	Colorless, viscous liquid
Ingredient	Modified Polydimethylsiloxane
Active Component	100%

BENEFITS

ADDSiL™ 5371 is suitable for water-based and medium-polarity or even high-polarity oil-based coating systems and can quickly defoam. ADDSiL™ 5371 has strong defoaming ability and performs well at low dosage levels.

APPLICATIONS

- Water based and middle/high polarity oil coating systems.

RECOMMENDED DOSAGE

The recommended dosage is 0.05-1.0% of the total formulations. The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

To achieve optimal defoaming, ADDSiL™ 5371 should be added in grinding stage.

PACKING

ADDSiL™ 5371 is supplied in 25Kg Pail.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, ADDSiL™ 5371 has a shelf life of 12 months from the date of production.

ADDSiL™ 5371 Silicone Defoamer

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.