

ADDSiL™ 5530 Silicone Defoamer

INTRODUCTION

ADDSiL™ 5530 is a universal organic silicone defoamer. It is highly cost effective and can be used in any step of the manufacture of paint.

ADDSiL™ 5530 is suitable for epoxy and UV coating systems.

PHYSICAL PROPERTIES

Color and Appearance	Colorless clear liquid
Ingredient	Silicone with defoam compound
Active Component	7%
Solvent	Paraffin

BENEFITS

- Excellent compatibility in oil coating;
- Suitable for low viscosity epoxy system
- Rapid defoaming;
- Outstanding defoam ability;
- Low possibility to cause crater

APPLICATIONS

ADDSiL™ 5530 is recommended for alkyd, acrylic, especially for epoxy and polyurethane oil coating systems, as well as solvent-free systems.

RECOMMENDED DOSAGE

The recommended dosage is 0.1-1.0% of the total formulations.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

PACKING

ADDSiL™ 5530 is supplied in 25Kg Pail.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, ADDSiL™ 5530 has a shelf life of 24 months from the date of production.

ADDSiL™ 5530 Silicone Defoamer

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.