

ADDSiL™ 5811 Silicone Defoamer

INTRODUCTION

ADDSiL™ 5811 is an organic silicone defoamer for water-based systems. It has strong defoaming ability with small dosage. It should be added in grinding stage.

PHYSICAL PROPERTIES

Color and Appearance	Colorless transparent liquid
Ingredient	Modified Polydimethylsiloxane
Content	100%

BENEFITS

- Suitable for water based and middle even high polarity oil coating system
- Fast defoaming ability, small dosage

APPLICATIONS

ADDSiL™ 5811 is recommended for use in both middle and high polarity oil coating systems, as well as water-based systems.

RECOMMENDED DOSAGE

The recommended dosage is 0.05-1.0% of the total formulations. The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

PACKING

ADDSiL™ 5811 is supplied in 25Kg Pail.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, ADDSiL™ 5811 has a shelf life of 24 months from the date of production.

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

ADDSiL™ 5811 Silicone Defoamer

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.