

ADDSiL™ 5825 Silicone Defoamer

INTRODUCTION

ADDSiL™ 5825 is an organic silicone emulsion as defoamer for water base systems with good antifoam ability at low dosage.

ADDSiL™ 5825 is easy to disperse and low possibility to cause crater.

PHYSICAL PROPERTIES

Color and Appearance	White emulsion
Ingredient	Modified silicone
Content	20%
Solvent	Water

BENEFITS

- Suit for water base coating systems;
- Good antifoam ability at low dosage;
- Low possibility to cause crater.

APPLICATIONS

ADDSiL™ 5825 is recommended to use in the water base coating systems.

RECOMMENDED DOSAGE

The recommended dosage is 0.05-1.0% of the total formulations.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

It is added during any stage of the production process including post-addition.

PACKING

ADDSiL™ 5825 is supplied in 25Kg Pail.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, ADDSiL™ 5825 has a shelf life of 24 months from the date of production.

ADDSiL™ 5825 Silicone Defoamer

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.