

## ADDSiL™ 5901 Silicone Defoamer

### INTRODUCTION

ADDSiL™ 5901 is an organic silicone emulsion type defoamer for water base systems. It has strong antifoaming without reverse influence on the coating film.

### PHYSICAL PROPERTIES

Color and Appearance	Turbid viscous liquid
Ingredient	Modified Polysiloxane
Content	100%

### BENEFITS

- Suitable for water-based coating system;
- Excellent defoaming ability;
- Low possibility to cause crater.

### APPLICATIONS

ADDSiL™ 5901 is suitable for water borne coating systems.

### RECOMMENDED DOSAGE

The recommended dosage is 0.1-1.0% of the total formulations. The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

It is added during any stage of the production process including post-addition.

### PACKING

ADDSiL™ 5901 is supplied in 25Kg metal Pail.

### HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

### STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, ADDSiL™ 5901 has a shelf life of 24 months from the date of production.

## ADDSiL™ 5901 Silicone Defoamer

### NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.