

# ADDSiL™ 5902 Silicone Defoamer

## INTRODUCTION

ADDSiL™ 5902 is an organic silicone emulsion type defoamer for water base systems. It has strong antifoaming without reverse influence on the coating film.

## PHYSICAL PROPERTIES

Color and Appearance	White emulsion
Ingredient	Modified Polysiloxane
Content	20%
Solvent	Water

## BENEFITS

- Suitable for water-based coating system;
- Fast defoaming ability;
- Low possibility to cause crater.

## APPLICATIONS

ADDSiL™ 5902 is suitable for water borne coating systems.

## RECOMMENDED DOSAGE

The recommended dosage is 0.05-1.0% of the total formulations. The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

## PACKING

ADDSiL™ 5902 is supplied in 25Kg metal Pail.

## HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

## STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, ADDSiL™ 5902 has a shelf life of 24 months from the date of production.

## NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

## ADDSiL™ 5902 Silicone Defoamer

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.