

KOBOND™ 8415 Polymeric Defoamer

INTRODUCTION

KOBOND™ 8415 is polymeric antifoaming agent with good compatibility and antifoam ability.

PHYSICAL PROPERTIES

Color and Appearance	Light yellow transparent liquid
Ingredient	Vinyl copolymer
Content	100%

APPLICATIONS

KOBOND™ 8415 can be used in polyester, polyurethane, epoxy and UV systems.

RECOMMENDED DOSAGE

The dosage of KOBOND™ 8415 is about 0.1% to 1.0% of the total dosage, please test the best dosage.

The dosage can be adjusted according to different systems and can be added at any stage of production.

PACKING

KOBOND™ 8415 is supplied in 25Kg pail.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, KOBOND™ 8415 has a shelf life of 24 months from the date of production.

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

KOBOND™ 8415 Polymeric Defoamer

We disclaim liability for any incidental or consequential damages.