

KOBOND™ 8437 Silicone Free Defoamer

INTRODUCTION

KOBOND™ 8437 is a mineral oil defoamer for water based systems.

KOBOND™ 8437 provides excellent antifoam property in grinding process.

BENEFITS / EFFECTS

- KOBOND™ 8437 is suit for water-based system.
- KOBOND™ 8437 should be introduced in any stage.

PHYSICAL PROPERTIES

Ingredient	Mineral Oil Emulsion
Appearance	White Emulsion
Content	50%

APPLICATIONS

KOBOND™ 8437 can be used in water-based systems.

RECOMMENDED DOSAGE

KOBOND™ 8437 should be added during the lapping stage of production, with a dosage ranging from 0.05% to 1.0% of the total mixture.

The dosage can be adjusted according to different systems and can be added at any stage of production.

PACKING

KOBOND™ 8437 is supplied in 25Kg pail.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, KOBOND™ 8437 has a shelf life of 24 months from the date of production.

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for

KOBOND™ 8437 Silicone Free Defoamer

a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.