

## **ADDSiL™ 1229 Silicone Leveling Agent**

#### **INTRODUCTION**

ADDSiL™ 1229 is polyether modified polysiloxane.

ADDSiL<sup>™</sup> 1229 can be used in most paint resins with excellent compatibility, no reverse influence on recoatibility.

ADDSiL<sup>™</sup> 1229 provides excellent leveling and antifoam stability when used in both solvent-born and water-born systems. It is especially suitable for polyurethane coatings.

#### **EFFECTS**

Leveling:	****
Wetting:	***
Recoat Ability:	****
Compatibility:	****
Slip effect:	****
Low Foaming Stability:	***
Anti-crater:	***
Anti-adhesive:	***

#### **PHYSICAL PROPERTIES**

Appearance	Yellowish Viscous Clear Liquid
Ingredient:	Polyether modified polysiloxane
Content (%):	100%

### **APPLICATIONS**

 ADDSiL<sup>™</sup> 1229 is suitable for both water-based and solvent-based systems.

#### **RECOMMENDED DOSAGE**

The recommended dosage is 0.1% ~ 1.0% of the total formulations.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

It is added during any stage of the production process including post-addition.

## **PACKING**

ADDSiL™ 1229 is supplied in 25Kg pail.

#### **HANDLING**

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website,



# **ADDSiL™ 1229 Silicone Leveling Agent**

from the distributor, or by contacting SiSiB customer service.

STORAGE When stored at temperatures between 10°C and 35°C in the original

unopened containers, ADDSiL  $^{\mbox{\tiny TM}}$  1229 has a shelf life of 24 months from the

date of production.

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to

 $technological\ progress\ or\ further\ developments.\ Performance\ of\ the\ product$ 

described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for

a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.