

ADDSiL™ 1351 Leveling Agent

INTRODUCTION

ADDSiL™ 1351 is an emulsion of high molecular weight silicone. It has excellent slipping and releasing effects in water-borne systems.

ADDSiL™ 1351 can improve the anti-scratch performance of the coating film.

EFFECTS

Leveling:	★★★
Wetting:	★★★
Recoat Ability:	★★★★★
Compatibility:	★★★
Slip effect:	★★★★★
Low Foaming Stability:	★★★★★
Anti-crater:	★★★
Anti-adhesive:	★★★★★

PHYSICAL PROPERTIES

Color and Appearance	White emulsion
Solvent:	Water
Active Ingredient	40%

APPLICATIONS

ADDSiL™ 1351 can be used in all water borne coatings.

RECOMMENDED DOSAGE

The recommended dosage to gross is 0.1~1.0% at random stage during the producing process.

PACKING

ADDSiL™ 1351 is supplied in 25Kg steel drum or according to customer's request.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

ADDSiL™ 1351 Leveling Agent

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.