

ADDSiL™ 1375 Silicone Leveling Agent

INTRODUCTION

ADDSiL™ 1375 is the solution of polyether modified polysiloxane which has excellent compatibility with most paint resins and it has no reverse influence on recoatability.

ADDSiL™ 1375 provides mar resistance for coating film and improves the gloss of the paint film.

EFFECTS

Leveling:	★★★★★
Wetting:	★★★★★
Recoat Ability:	★★★★★
Compatibility:	★★★★★
Slip effect:	★★★★★
Low Foaming Stability:	★★
Anti-crater:	★★★★★
Anti-adhesive:	★★★★★

PHYSICAL PROPERTIES

Color and Appearance	Colorless transparent liquid
Ingredient	Polyether modified polysiloxane
Solvent	2-(propoxyethoxy)ethanol
Content	50%

APPLICATIONS

- Solvent-based coating

RECOMMENDED DOSAGE

The recommended dosage is 0.1% ~ 1.0% during the production.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

PACKING

ADDSiL™ 1375 is supplied in 25Kg plastic pail.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

ADDSiL™ 1375 Silicone Leveling Agent

STORAGE

In the original unopened packaging, ADDSiL™ 1375 has a shelf life of 24 months.

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.