

ADDSiL™ 6250 Silicone Leveling Agent

INTRODUCTION

ADDSiL™ 6250 is polyether modified polysiloxane with acrylic group, it has excellent compatibility with most paint resins and it could provide excellent leveling and slip in UV systems.

EFFECTS

Leveling:	★★★★★
Wetting:	★★★★
Recoat Ability:	★★★★★
Compatibility:	★★★★★
Slip effect:	★★★★★
Low Foaming Stability:	★★
Anti-crater:	★★★★
Anti-adhesive:	★★★★

PHYSICAL PROPERTIES

Color and Appearance	Light yellow viscous transparent liquid
Ingredient	Polyether modified polysiloxane with acrylic group
Content	100%

APPLICATIONS

- UV coatings.

RECOMMENDED DOSAGE

The recommended dosage is 0.1% ~ 1.0% during the production.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

It is added during any stage of the production process including post-addition.

PACKING

ADDSiL™ 6250 is supplied in 25Kg steel drum or according to customer's request.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical

ADDSiL™ 6250 Silicone Leveling Agent

hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

In the original unopened packaging, ADDSiL™ 6250 has a shelf life of 12 months.

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.