

ADDSiL™ 6350 Silicone Leveling Agent

INTRODUCTION

ADDSiL™ 6350 is polyether modified, acrylic functional polysiloxane.

PHYSICAL PROPERTIES

Color and Appearance	Yellow viscous transparent liquid
Ingredient	Polyether modified, acrylic functional polysiloxane
Content	100%

BENEFITS

- Superb substrate wetting.
- Excellent leveling and sliding
- Great recoat ability and compatibility
- Good anti-adhesive ability and anti-crater ability
- Improve the low foaming stability

APPLICATIONS

- UV coatings.

RECOMMENDED DOSAGE

The recommended dosage is 0.1% ~ 1.0% during the production.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

It is added during any stage of the production process including post-addition.

PACKING

ADDSiL™ 6350 is supplied in 25Kg pail.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

In the original unopened packaging, ADDSiL™ 6350 has a shelf life of 12 months.

ADDSiL™ 6350 Silicone Leveling Agent

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.