

KOBOND™ 810 Hammer Agent

INTRODUCTION

KOBOND™ 810 is a type of organic polymer, it's Water-Based Hammer Grain Additive and Orange Grain Additive.

BENEFITS / EFFECTS

- Excellent pattern effect when used in the coating
- Producing stronger three-dimensional patterns
- Good thixotropy, which can fix the pattern quickly after the pattern is formed to prevent leveling

PHYSICAL PROPERTIES

Color and Appearance	Colorless to yellowish transparent liquid
Active ingredient:	35%
Specific gravity (25°C, g/ml)	0.89-0.91

APPLICATIONS

- KOBOND™ 810 can be used in water-based self-drying system.
- KOBOND™ 810 can be used in waterborne PU two-component system.
- KOBOND™ 810 can be used in waterborne amino baking paint system.

RECOMMENDED DOSAGE

The dosage of KOBOND™ 810 is about 0.2-0.8% of the total dosage, please test the best dosage.

PACKING

KOBOND™ 810 is supplied in net weight 25Kg or 50Kg pail.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, KOBOND™ 810 has a shelf life of 24 months from the date of production.

KOBOND™ 810 Hammer Agent

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.