

KOBOND™ 8357 Leveling Agent

INTRODUCTION

KOBOND™ 8357 is fluorocarbon modified acrylic copolymer leveling agent which has excellent leveling performance and fast leveling speed.

KOBOND™ 8357 can provide good anti-crater ability by reducing the surface tension on the paint film.

BENEFITS

KOBOND™ 8357 has excellent compatibility and good leveling in solvent system.

KOBOND™ 8357 can decrease the surface tension and improve the substrate wetting.

PHYSICAL PROPERTIES

| | |
|----------------------|-------------------------------|
| Color and Appearance | Colorless transparent liquid |
| Ingredient | Fluorinated acrylic copolymer |
| Solvent | solvent naphtha |
| Content | 70% |

APPLICATIONS

KOBOND™ 8357 is recommended to be applied in solvent and solvent-free systems such as alkyd, acrylic acid, amino baking.

RECOMMENDED DOSAGE

The recommended dosage is 0.1% ~ 1.0% during the production.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

PACKING

KOBOND™ 8357 is supplied in 25Kg Pail.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

In the original unopened packaging, KOBOND™ 8357 has a shelf life of 24 months.

KOBOND™ 8357 Leveling Agent

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.