

## KOBOND™ 8363 Leveling Agent

### INTRODUCTION

KOBOND™ 8363 is an acrylic copolymer leveling agent with 100% content, which is widely used in car- refinish, UV coating.

### BENEFITS

KOBOND™ 8363 has good compatibility and excellent leveling

KOBOND™ 8363 can reduce the surface tension and anti-crater.

### PHYSICAL PROPERTIES

Color and Appearance	Colorless to light yellow transparent liquid
Ingredient	Acrylic copolymer
Content	100%

### APPLICATIONS

KOBOND™ 8363 is applied in the alkyd, acrylic, amino baking paint and polyurethane solvent-borne systems and solvent-free systems.

### RECOMMENDED DOSAGE

The recommended dosage is 0.1% ~ 1.0% during the production.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

### PACKING

KOBOND™ 8363 is supplied in 25Kg pail.

### HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

### STORAGE

In the original unopened packaging, KOBOND™ 8363 has a shelf life of 24 months.

### NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

## **KOBOND™ 8363 Leveling Agent**

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.