

KOBOND™ 8381 Leveling Agent

INTRODUCTION

KOBOND™ 8381 is modified acrylic copolymer leveling agent which is suitable for water-borne systems.

KOBOND™ 8381 can provide the excellent leveling for the paint.

BENEFITS

KOBOND™ 8381 has excellent compatibility and good leveling in water-borne system.

KOBOND™ 8381 can decrease the surface tension on the paint film and improve the substrate wetting.

PHYSICAL PROPERTIES

Color and Appearance	Yellow transparent liquid
Ingredient	Acrylic copolymer
Solvent	Dipropylene Glycol Methyl Ether
Content	50%

APPLICATIONS

KOBOND™ 8381 is applied in all water-based systems such as alkyd, acrylic acid, amino baking.

KOBOND™ 8381 could be charged at random stage during the produce with 0.1% to 1.0% dosage to gross.

RECOMMENDED DOSAGE

The recommended dosage is 0.1% ~ 1.0% during the production.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

PACKING

KOBOND™ 8381 is supplied in 25Kg Pail.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

In the original unopened packaging, KOBOND™ 8381 has a shelf life of 24

KOBOND™ 8381 Leveling Agent

months.

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.