KOBOND™ 8399 Acrylic Copolymer Leveling Agent

INTRODUCTION

KOBOND™ 8399 is an acrylic copolymer leveling agent. It is mainly dedicated for use in solvent-based coating and UV coating.

BENEFITS

- Good compatibility and leveling
- Reduce the surface tension and improve wetting and anti-crater
- Organo silane and fluoro free

PHYSICAL PROPERTIES

Ingredient:	Solution mixture of high boiling
	point organic solvent
Appearance:	Colorless to yellowish transparent
	liquid
Content:	100%

APPLICATIONS

KOBOND[™] 8399 can be used in the alkyd, acrylic, amino baking paint and polyurethane oil coating systems, as well as those solvent free systems.

RECOMMENDED DOSAGE

It could be charged at random stage during the produce with 0.1% to 1% dosage to gross.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

PACKING

KOBOND™ 8399 is supplied in 25Kg pail.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

In the original unopened packaging, KOBOND™ 8399 has a shelf life of 24 months.

KOBOND™ 8399 Acrylic Copolymer Leveling Agent

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.