

ADDSiL[™] 3008 Silicone Wetting Agent

INTRODUCTION

ADDSiL[™] 3008 is polyether modified organic silicon compound. It can greatly decrease the surface tension and provide the strength wetting ability and without any influence on the recoat ability.

EFFECTS	Leveling:	****
	Wetting:	****
	Recoat Ability:	****
	Compatibility:	****
	Slip effect:	*
	Low Foaming Stability:	**
	Anti-crater:	****
	Anti-adhesive:	*
BENEFITS	 Suitable for the aqueous wood lacquer, printing ink and radiation curing systems Excellent substrate wetting and flatting agent with great anti-hydrolysis ability 	
APPLICATIONS	ADDSiL [™] 3008 is suitable for the water-wood-paint, industry water-borne coatings and UV-curable coatings, printing ink systems.	
RECOMMENDED DOSAGE	The recommended dosage is 0.1% ~ 1.0% of the total formulations. The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests. It is added during any stage of the production process including post- addition.	
PACKING	ADDSiL [™] 3008 is supplied in 25Kg / 200Kg plastic drum or steel drum or according to customer's request.	
HANDLING	This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.	

SINOPCC GROUP

Product Data Sheet - Page 1/2 ADDSiL[™] 3008 December 2024, Version 8.1, D-R Copyright © SiSiB SILICONES. Affiliate of SINOPCC GROUP. www.sinosil.com



ADDSiL[™] 3008 Silicone Wetting Agent

STORAGE	When stored at temperatures between 10°C and 35°C in the original unopened containers, ADDSiL™ 3008 has a shelf life of 24 months from the date of production.
NOTE	All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.
	We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.

SINOPCC GROUP

Product Data Sheet - Page 2/2 ADDSiL[™] 3008 December 2024, Version 8.1, D-R Copyright © SiSiB SILICONES. Affiliate of SINOPCC GROUP. www.sinosil.com