

ADDSiL™ 3023 Substrate Wetting Agent

INTRODUCTION

ADDSiL™ 3023 is polyether modified organic polysiloxane which can reduce the surface tension.

ADDSiL™ 3023 can provide excellent substrate wetting and low foam stability in water-borne coating and ink systems.

EFFECTS

Leveling:	★★★★★
Wetting:	★★★★★
Recoat Ability:	★★★★★
Compatibility:	★★★★★
Slip effect:	★
Low Foaming Stability:	★★★★★
Anti-crater:	★★★★★
Anti-adhesive:	★

PHYSICAL PROPERTIES

Color and Appearance	Yellowish clear liquid
Ingredient	Polyether modified Silicone
Content	100%

APPLICATIONS

- Water-borne wood coatings
- Water-borne industry coatings
- UV-curable coatings
- Printing ink systems

RECOMMENDED DOSAGE

The recommended dosage is 0.1% ~ 1.0% of the total formulations.

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

It is added during any stage of the production process including post-addition.

PACKING

ADDSiL™ 3023 is supplied in 25Kg plastic pail.

HANDLING

This document does not contain the product safety information required for safe use. Before handling, please refer to the product and safety data sheets, as well as container labels, for information on safe usage, physical

ADDSiL™ 3023 Substrate Wetting Agent

hazards, and health risks. Safety Data Sheet is available on the website, from the distributor, or by contacting SiSiB customer service.

STORAGE

When stored at temperatures between 10°C and 35°C in the original unopened containers, ADDSiL™ 3023 has a shelf life of 24 months from the date of production.

NOTE

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.