

ADDSiL™ 11930

Silicone Surfactant for Polyurethane Sole

INTRODUCTION

ADDSiL™ 11930 is silicone surfactant for most conventional rigid polyurethane foam and shoe sole systems.

FEATURES

- Non-hydrolyzable chemical structure for improved premix stability
- Good compatibility with most regular polyol premixes.

TYPICAL PHYSICAL PROPERTIES

Appearance	Clear liquid
Viscosity _{25°C}	300+/-100 mPa.s
Density _{25°C}	1.07+/-0.02 g/cm ³
Water Solubility	Soluble

APPLICATIONS

ADDSiL™ 11930 can be used in most rigid foam applications including laminated boardstock, spray foam, packaging, bunstock and most pour-in-place systems.

ADDSiL™ 11930 can also be used in shoe sole applications.

Typical use levels are 1% - 3% pphp.

PACKING AND STORAGE

ADDSiL™ 11930 is supplied in net weight 200Kg steel drum or 1050Kg IBC tote.

When stored at ambient temperature in the original unopened packings, ADDSiL™ 11930 has a shelf life of 24 months from the date of production.

NOTES

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further

ADD*SiL*TM 11930

Silicone Surfactant for Polyurethane Sole

developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

August 2024 | [Technical Data Sheet](#) | [Edition SR](#)

Please send all technical questions concerning quality and product safety to:
support@SiSiB.com.