

ADDSiL™ 13800

Silicone Surfactant

INTRODUCTION

ADDSiL™ 13800 is a medium-potency silicone surfactant, designed to provide excellent foam stability and fine regular cell structure for flexible slabstock foam.

SPECIAL FEATURES AND BENEFITS

- Brings well cell stabilization in flexible PU foam blocks with minimum sink back.
- Provide increased foam height with open cell characteristics.
- Suitable on virtually all types of foam machines.

TYPICAL PHYSICAL PROPERTIES

Appearance	Light yellow liquid
Viscosity _{25°C}	1025+/-175 cSt
Specific Gravity _{25°C}	1.02+/-0.02 g/cm ³
Water Solubility	Soluble

APPLICATIONS

ADDSiL™ 13800 is used in low to medium density flexible foam production, typical foam densities are 10-40 kg/m³.

PACKING AND STORAGE

ADDSiL™ 13800 is supplied in net weight 210Kg steel drum or 1050Kg IBC tote.

When stored at ambient temperature in the original unopened packing, ADDSiL™ 13800 has a shelf life of 12 months from the date of production.

NOTES

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

ADD*Si*L™ 13800

Silicone Surfactant

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

Please send all technical questions concerning quality and product safety to: support@SiSiB.com.