

ADDSiL™ 13902

Silicone Surfactant for Flexible Polyurethane Foam

INTRODUCTION

ADDSiL™ 13902 is a polyalkyleneoxide modified polysiloxane surfactant which is designed for flexible PU foam.

FEATURES

- Provides good breathability
- Low-medium potency, recommended for density min.20 Kg/m³ formulation or density 40 Kg/m³~80 Kg/m³ based TDI VE foam formulation

TYPICAL PHYSICAL PROPERTIES

Appearance	Viscous Liquid
Viscosity _{25°C}	700+/200 cSt
Density _{25°C}	1.03 g/cm ³
Flash Point	>96 °C

PACKING AND STORAGE

ADDSiL™ 13902 is supplied in net weight 210Kg steel drum or 1000Kg IBC tote.

When stored at ambient temperature in the original unopened packing, ADDSiL™ 13902 has a shelf life of 24 months from the date of production.

NOTES

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

Please send all technical questions concerning quality and product safety to: support@SiSiB.com.