

### CHEMICAL STRUCTURE

$$H_2C \longrightarrow CH \longrightarrow Si \longrightarrow OC_2H_5$$
 $CH_3$ 

#### INTRODUCTION

SiSiB® PC6220 is a clear to straw liquid.

## TYPICAL PHYSICAL PROPERTIES

CAS No.	5356-83-2
EINECS No.	226-341-7
Formula	C <sub>6</sub> H <sub>14</sub> OSi
Molecular Weight	130.26
Boiling Point	100°C [760mmHg]
Flash Point	4°C
Color and Appearance	Colorless transparent liquid
Density <sub>25/25°C</sub>	0.79
Refractive Index	1.3983 [25°C]
Min. Purity	99.0%

### APPLICATIONS

SiSiB® PC6220 can be used as end capping agent for vinyl silicone fluid and silicone rubber.

### PACKING AND STORAGE

SiSiB® PC6220 is supplied in net weight 160Kg steel drum.

In the unopened original container SiSiB® PC6220 has a shelf life of one year in a dry

SINOPCC GROUP

AddSil, CoatSil, Kolark, PowSil, SinoSil, SiSiB, WinSil: Trademark of SINOPCC Group Limited or its affiliated. © 2018 SINOPCC Group Limited. All rights reserved. For further information, please see www.SiSiB.com.

# SiSiB® PC6220 Vinyldimethylethoxysilane

and cool place.

### Notes

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability. We disclaim liability for any incidental or consequential damages.

Please send all technical questions concerning quality and product safety to: silanes@SiSiB.com.



AddSil, CoatSil, Kolark, PowSil, SinoSil, SiSiB, WinSil: Trademark of SINOPCC Group Limited or its affiliated. © 2018 SINOPCC Group Limited. All rights reserved. For further information, please see www.SiSiB.com.